

Classic range	code	Min overall size (equal split)		Minimum panel size		Max size: 4mm glass		Max size: 6mm or laminate		Max glass thickness
		width	height	width	height	width	height	width	height	
2 pane horizontal slider	SS2	400	250	half min overall size		2400	1800	2400	2000	6.8
3 pane horizontal slider	SS3/CO3	550	250	half min overall size		3600	1800	3600	2000	6.8
4 pane horizontal slider	SS4	700	250	half min overall size		4900	1800	4900	2000	6.8
5 pane horizontal slider	SS5	850	250	half min overall size		4900	1800	4900	2000	6.8
Insert	INS	200	200			1200	2000	2000	2000	6.8
Balanced vertical slider	BVS	300	600	half min overall size		1500	3000	1500	3000	6.8
Tilt in balanced vertical slider	TBVS	300	700	half min overall size		1500	3000	1400	2700	6.8
Lift out	LO	250	300			2000	2000	2000	2200	6.8
Slim-line lift out	SL-LO	250	300			1200	2000	2000	2200	6.8

Forte range	code	width	height	width	height	width	height	width	height	mm
2 pane horizontal slider	HSS2	1000	500	half min overall size		4900	2700	4900	2700	8.8
3 pane horizontal slider	HSS3/HC03	1500	500	half min overall size		4900	2700	4900	2700	8.8
4 pane horizontal slider	HSS4	2000	500	half min overall size		4900	2700	4900	2700	8.8
5 pane horizontal slider	HSS5	2500	500	half min overall size		4900	2700	4900	2700	8.8
Balanced vertical slider	HBVS	400	900	half min overall size		1500	3000	1400	3000	8.8
Tilt in balanced vertical silder	HTBVS	400	900	half min overall size		1500	3000	1400	3000	8.8
Hinge unit	HHU	350	500			1400	2400	1500	3000	28
Hinge unit + tilt and turn	HHU-TT	600	500			1400	2400	1400	2400	28
Double hinge unit	DHHU	700	500			2800	2800	3000	3000	28
Slim-line lift out	HSLO	500	500							8.8

Important: Maximum sizes are for width OR height, not combined. Calculate glass weight and do not exceed the maximum panel weight.

1 Calculate glass weight and do not exceed the maximum panel weight.

2 Maximum area for 4mm glass is 1.6m². If panel size exceeds this, allow for 4mm toughened glass. Maximum area for 6mm glass is 3.0m². If panel size exceeds this, allow for 6mm toughened glass.

3 Flyscreens: maximum size 1200mm in one direction

Classic range	code	Min overall size (equal split)		Minimum panel size		Max size: 4mm glass		Max size: 6mm or laminate		Grey area: 6mm or laminate		Max glass thickness
		width	height	width	height	width	height	width	height	width	height	
2 pane horizontal slider	SS2	400	250	half min overall size		2400	1800	2400	2000	2800	2500	6.8
3 pane horizontal slider	SS3/CO3	550	250	half min overall size		3600	1800	3600	2000	4200	2500	6.8
4 pane horizontal slider	SS4	700	250	half min overall size		4900	1800	4900	2000	4900	2500	6.8
5 pane horizontal slider	SS5	850	250	half min overall size		4900	1800	4900	2000	4900	2500	6.8
Insert	INS	200	200			1200	2000	2000	2000	2000	2500	6.8
Vertical slider	VS	300	250	half min overall size		800	1500	800	1500			6.8
Balanced vertical slider	BVS	300	600	half min overall size		1500	3000	1500	3000	1600	3600	6.8
Tilt in balanced vertical slider	TBVS	300	700	half min overall size		1500	3000	1400	2700	1400	3000	6.8
Hinge unit	HU	300	300			1200	1800	1200	1800			6.8
Lift out	LO	250	300			2000	2000	2000	2200	2000	2500	6.8
Slim-line lift out	SL-LO	250	300			1200	2000	2000	2200	2000	2700	6.8

Forte range	code	width	height	width	height	width	height	width	height	width	height	mm
2 pane horizontal slider	HSS2	1000	500	half min overall size		4900	2700	4900	2700			8.8
3 pane horizontal slider	HSS3/HC03	1500	500	half min overall size		4900	2700	4900	2700			8.8
4 pane horizontal slider	HSS4	2000	500	half min overall size		4900	2700	4900	2700			8.8
5 pane horizontal slider	HSS5	2500	500	half min overall size		4900	2700	4900	2700			8.8
Balanced vertical slider	HBVS	400	900	half min overall size		1500	3000	1400	3000	1800	3800	8.8
Tilt in balanced vertical slider	HTBVS	400	900	half min overall size		1500	3000	1400	3000	1500	3200	8.8
Hinge unit	HHU	350	500			1400	2400	1500	3000	1600	3800	28
Hinge unit + tilt and turn	HHU-TT	600	500			1400	2400	1400	2400	1400	2400	28
Double hinge unit	DHHU	700	500			2800	2800	3000	3000	3200	3800	28
Slim-line lift out	HSLO	500	500									8.8

Important: Maximum sizes are for width OR height, not combined. Calculate glass weight and do not exceed the maximum panel weight.

1 Windows in the grey areas exceed our recommended size limit. We will make windows to these sizes but give no performance guarantee and accept your order solely on this basis.

Alternatively, re-design the window to comply with recommended sizes to benefit from the full product warranty.

2 Calculate glass weight and do not exceed the maximum panel weight.

3 Maximum area for 4mm glass is 1.6m². If panel size exceeds this, allow for 4mm toughened glass. Maximum area for 6mm glass is 3.0m². If panel size exceeds this, allow for 6mm toughened glass.

4 Horizontal sliders between 1800-2000mm high have 21243 medium strengthening interlock added at no extra cost. Horizontal sliders over 2000mm high need 37015 heavy duty interlock at extra cost (subframe will be minimum 50mm deep)

5 Flyscreens: maximum size 1200mm in one direction

Clear View Secondary Glazing Omnia One, Queen Street, Sheffield S1 2DU Tel: 0114 294 5018 Fax: 0114 279 2601 info@clearviewsg.co.uk www.clearviewsg.co.uk

A division of Connection Products Ltd. Registered Office: 51 Clarkegrove Road, Sheffield S10 2NH Company Registration No. 5409439 VAT No. 856 9355 74

